



Institutional Castors



Grey Thermoplastic Rubber Institutional Castors

Technical Information:

Housing: pressed steel fork assembly, zinc-plated swivel head with double ball race and sealing
Wheel: grey polypropylene wheel centre dark grey shore a 85"thermoplastic rubber tread, plain bore



Swivel Castor

									Order number
	75	28	77x67	55.7x46.5	16x8.5	30.5	103	75	18P1S75D28DTPPX3612
	75	28	105x80	80x60	16x8.5	30.5	103	75	18P1S/S75D28DTPPX3612
	100	32	77x67	55.7x46.5	16x8.5	40	137	100	18P1S100D32DTPPX3612
	100	32	105x80	80x60	16x8.5	40	137	100	18P1S/S100D32DTPPX3612
	125	32	77x67	55.7x46.5	16x8.5	43	162	100	18P1S125D32DTPPX3612
	125	32	105x80	80x60	16x8.5	43	162	100	18P1S/S125D32DTPPX3612

Fixed Castor

								Order number
	75	28	77x67	55.7x46.5	16x8.5	103	75	18P1F75D28DTPPX3612
	75	28	105x80	80x60	16x8.5	103	75	18P1F/S75D28DTPPX3612
	100	32	77x67	55.7x46.5	16x8.5	137	100	18P1F100D32DTPPX3612
	100	32	105x80	80x60	16x8.5	137	100	18P1F/S100D32DTPPX3612
	125	32	77x67	55.7x46.5	16x8.5	162	100	18P1F125D32DTPPX3612
	125	32	105x80	80x60	16x8.5	162	100	18P1F/S125D32DTPPX3612

Swivel Castor With Total Lock

									Order number	
	75	28	77x67	55.7x46.5	16x8.5	30.5	98.5	103	75	18P1TB75D28DTPPX3612
	75	28	105x80	80x60	16x8.5	30.5	98.5	103	75	18P1TB/S75D28DTPPX3612
	100	32	77x67	55.7x46.5	16x8.5	40	112	137	100	18P1TB100D32DTPPX3612
	100	32	105x80	80x60	16x8.5	40	112	137	100	18P1TB/S100D32DTPPX3612
	125	32	77x67	55.7x46.5	16x8.5	43	118	162	100	18P1TB125D32DTPPX3612
	125	32	105x80	80x60	16x8.5	43	118	162	100	18P1TB/S125D32DTPPX3612

Swivel Castor With Total Lock

									Order number	
	75	28	77x67	55.7x46.5	16x8.5	30.5	98.5	103	75	18P1TB75D28DTPPX3612
	75	28	105x80	80x60	16x8.5	30.5	98.5	103	75	18P1TB/S75D28DTPPX3612
	100	32	77x67	55.7x46.5	16x8.5	40	112	137	100	18P1TB100D32DTPPX3612
	100	32	105x80	80x60	16x8.5	40	112	137	100	18P1TB/S100D32DTPPX3612
	125	32	77x67	55.7x46.5	16x8.5	43	118	162	100	18P1TB125D32DTPPX3612
	125	32	105x80	80x60	16x8.5	43	118	162	100	18P1TB/S125D32DTPPX3612

Grey Thermoplastic Rubber Institutional Castors

Technical Information:

Housing: pressed steel fork assembly, zinc-plated swivel head with double ball race and sealing
Wheel: grey polypropylene wheel centre dark grey shore a 85"thermoplastic rubber tread, plain bore



Swivel Castor With Bolt Hole

							Order number
	75	28	30.5	φ10.3/φ13	100.5	75	18H1S75D28DTPPX3612
	100	32	40	φ10.3/φ13	134.5	100	18H1F100D32DTPPX3612
	125	32	43	φ10.3/φ13	159.5	100	18H1F125D32DTPPX3612

Swivel Castor With Bolt Hole And Total Lock

								Order number
	75	28	30.5	φ10.3/φ13	98.5	100.5	75	18H1TB75D28DTPPX3612
	100	32	40	φ10.3/φ13	112	134.5	100	18H1TB100D32DTPPX3612
	125	32	43	φ10.3/φ13	118	159.5	100	18H1TB125D32DTPPX3612

Swivel Castor With Bolt Hole And Total Lock


								Order number
	75	28	30.5	φ10.3/φ13	98.5	100.5	75	18H1TB75D28DTPPX3612
	100	32	40	φ10.3/φ13	112	134.5	100	18H1TB100D32DTPPX3612
	125	32	43	φ10.3/φ13	118	159.5	100	18H1TB125D32DTPPX3612

Grey Thermoplastic Rubber Institutional Castors

Technical Information:

Housing: pressed steel fork assembly, zinc-plated swivel head with double ball race and sealing

Wheel: grey polypropylene wheel centre dark grey shore a 85° thermoplastic rubber tread, central ball bearing, grey plastic thread guards



	-20 / +60°C		4 KM/H
	75 - 100 KG		103 - 162MM

Swivel Castor



								Order number
75	28	77x67	55.7x46.5	16x8.5	30.5	103	75	18P1S75D28DTPBB378
75	28	105x80	80x60	16x8.5	30.5	103	75	18P1S/S75D28DTPBB378
100	32	77x67	55.7x46.5	16x8.5	40	137	100	18P1S100D32DTPBB378
100	32	105x80	80x60	16x8.5	40	137	100	18P1S/S100D32DTPBB378
125	32	77x67	55.7x46.5	16x8.5	43	162	100	18P1S125D32DTPBB378
125	32	105x80	80x60	16x8.5	43	162	100	18P1S/S125D32DTPBB378

Fixed Castor



							Order number
75	28	77x67	55.7x46.5	16x8.5	103	75	18P1F75D28DTPBB378
75	28	105x80	80x60	16x8.5	103	75	18P1F/S75D28DTPBB378
100	32	77x67	55.7x46.5	16x8.5	137	100	18P1F100D32DTPBB378
100	32	105x80	80x60	16x8.5	137	100	18P1F/S100D32DTPBB378
125	32	77x67	55.7x46.5	16x8.5	162	100	18P1F125D32DTPBB378
125	32	105x80	80x60	16x8.5	162	100	18P1F/S125D32DTPBB378

Swivel Castor With Total Lock



									Order number
75	28	77x67	55.7x46.5	16x8.5	30.5	98.5	103	75	18P1TB75D28DTPBB378
75	28	105x80	80x60	16x8.5	30.5	98.5	103	75	18P1TB/S75D28DTPBB378
100	32	77x67	55.7x46.5	16x8.5	40	112	137	100	18P1TB100D32DTPBB378
100	32	105x80	80x60	16x8.5	40	112	137	100	18P1TB/S100D32DTPBB378
125	32	77x67	55.7x46.5	16x8.5	43	118	162	100	18P1TB125D32DTPBB378
125	32	105x80	80x60	16x8.5	43	118	162	100	18P1TB/S125D32DTPBB378

Swivel Castor With Total Lock




									Order number
75	28	77x67	55.7x46.5	16x8.5	30.5	98.5	103	75	18P1TB75D28DTPBB378
75	28	105x80	80x60	16x8.5	30.5	98.5	103	75	18P1TB/S75D28DTPBB378
100	32	77x67	55.7x46.5	16x8.5	40	112	137	100	18P1TB100D32DTPBB378
100	32	105x80	80x60	16x8.5	40	112	137	100	18P1TB/S100D32DTPBB378
125	32	77x67	55.7x46.5	16x8.5	43	118	162	100	18P1TB125D32DTPBB378
125	32	105x80	80x60	16x8.5	43	118	162	100	18P1TB/S125D32DTPBB378

Grey Thermoplastic Rubber Institutional Castors

Technical Information:

Housing: pressed steel fork assembly, zinc-plated swivel head with double ball race and sealing

Wheel: grey polypropylene wheel centre dark grey shore a 85° thermoplastic rubber tread, central ball bearing, grey plastic thread guards



	-20 / +60°C		4 KM/H
	75 - 100 KG		100.5-159.5MM

Swivel Castor With Bolt Hole



						Order number
75	28	30.5	φ10.3/φ13	100.5	75	18H1S75D28DTPBB378
100	32	40	φ10.3/φ13	134.5	100	18H1S100D32DTPBB378
125	32	43	φ10.3/φ13	159.5	100	18H1S125D32DTPBB378

Swivel Castor With Bolt Hole And Total Lock



							Order number
75	28	30.5	φ10.3/φ13	98.5	100.5	75	18H1TB75D28DTPBB378
100	32	40	φ10.3/φ13	112	134.5	100	18H1TB100D32DTPBB378
125	32	43	φ10.3/φ13	118	159.5	100	18H1TB125D32DTPBB378

Swivel Castor With Bolt Hole And Total Lock




							Order number
75	28	30.5	φ10.3/φ13	98.5	100.5	75	18H1TB75D28DTPBB378
100	32	40	φ10.3/φ13	112	134.5	100	18H1TB100D32DTPBB378
125	32	43	φ10.3/φ13	118	159.5	100	18H1TB125D32DTPBB378

Grey Thermoplastic Rubber Institutional Castors

Technical Information:

Housing: pressed steel fork assembly, zinc-plated swivel head with double ball race and sealing

Wheel: grey polypropylene wheel centre dark grey shore a 85° thermoplastic rubber tread, plain bore, metal thread guards



-20 / +60°C
 4 KM/H
 75 - 100 KG
 97 - 139MM

Adjustable Swivel Castor



								Order number
75	28	96x90	77/55x70	10.2	30.5	97-106	75	18P1S/S75D28DTPPD3612
100	32	96x90	77/55x70	10.2	40	118-127	100	18P1S/S100D32DTPPD3612
125	32	96x90	77/55x70	10.2	43	130-139	100	18P1S/S125D32DTPPD3612

Adjustable Fixed Castor



							Order number
75	28	96x90	77/55x70	10.2	97-106	75	18P1F/S75D28DTPPD3612
100	32	96x90	77/55x70	10.2	118-127	100	18P1F/S100D32DTPPD3612
125	32	96x90	77/55x70	10.2	130-139	100	18P1F/S125D32DTPPD3612

Adjustable Swivel Castor With Total Lock



									Order number
75	28	96x90	77/55x70	10.2	30.5	100.5	97-106	75	18P1TB/S75D28DTPPD3612
100	32	96x90	77/55x70	10.2	40	113.5	118-127	100	18P1TB/S100D32DTPPD3612
125	32	96x90	77/55x70	10.2	43	120.5	130-139	100	18P1TB/S125D32DTPPD3612